

Electronic Laser Detector with Rod Clamp

- Front and rear LCD displays
- Compatible with most visible and invisible rotary lasers
- Memory feature preserves last position of beam if the unit is moved out of the plane of light
- Three distinct tones (high, on-grade, and low) assist targeting from a distance
- Automatic shut-off after six minutes of inactivity saves battery
- Waterproof to IPX-4 standards



EDP#	CONTENTS	WARRANTY
77-169	RLD4 Laser Detector. Includes rod clamp, 9V battery	1

RL 100 Dual Beam Horizontal/Vertical Rotary Laser

Ideal for leveling and aligning indoors and outdoors, single button dual beam rotary laser delivers accurate readings up to 1/4-in at 100 feet. Vertical layout position with 5/8-11 thread mounting.

- Two screw manual leveling with dual 5/8-11 thread mounting for both horizontal and vertical
- Short and long chalkline
- Variable speed– 150, 600RPM with spot mode
- Low battery alarm
- Three precise leveling vials
- Auto shut off Anti Drift System
- Scanning mode
- Level / Plumb Beam



EDP#	LASER DIODE	ACCURACY	WORKING RANGE	SELF LEVELING	ROTARY SPEED (RPM)
77-156	635 - 670nm (Class 2M)	Indoors– Up to 200 ft (61m) Outdoors– Up to 800 ft (244m) with detector (optional)	24m	Manual	150,600

EDP#	CONTENTS	POWER
77-156	RL100 Interior Package Includes: Interior Package-remote control, wall mount bracket, magnetic target plate, laser glasses, battery charger, carrying case	3 "C" cell Alkaline batteries



FatMax® CL54-Multi Laser Cross Level (Not below 55)

Quickly Level, Plumb and Align: Doors and Frames, Cabinets and Shelving, Drop Ceilings, Wainscoting and Paneling, Wall Hangings, Pipe and Conduit, Floor and Wall Tiles, Installing Closets, Interior Decoration, Finish Carpentry, Masonry Work, Wall Fixtures, Wall Studs, Partitions and More

- 4 Laser-crosses at 90° to each other
- Laser-cross to the ceiling
- Plumb down beam to the floor
- Select 4 visible laser lines individually
- Solid magnetic dampening
- Adjustable 360° circle reading
- Tangent screw—for fine tune adjustment
- Compensator-lock for transport
- Visible alarm when out of level
- Use with floor trivet, removable, also mount to 5/8-11 thread

EDP#	LASER DIODE	LEVELING ACCURACY	WORKING RANGE	SELF LEVELING	POWER	WARRANTY
77-204	5 x 635nm (Class 2M) 1 x 650nm (Class 2M)	Horiz./Vertical Lines: 3.2mm@10m Laser Cross (Ceiling): 3.2mm@10m Plumb down Beam: 6.4mm@15.2m 90 degree verticals: ±1 minute	Up to 32 ft (10m)	± 3.5"	3 Ni-MH "C" batteries with charger	1

