


FatMax® CL2XT Interior - Exterior Cross Line Laser Level

Ideal for floor and wall tiling, paneling, wall fixtures, wallpapering, stenciling, wainscoting, finish carpentry, masonry work, cabinets and shelving, drop ceilings, outlet switches, lighting fixtures, wall studs, partitions, patios, decks, and much more!

- Projects bright, self-leveling level and plum laser "chalkline" for instant, accurate reference marks
- Use OUTDOORS with Line Detector - included with CL2XTD (77-222)
- 4X Brighter Beam, Higher Precision
- Built for Exterior and Interior Use
- 'Manual Mode Feature'
- Out-of-level-sensor



EDP#	LASER DIODE	ACCURACY	WORKING RANGE	SELF LEVELING	SLOPE CAPACITY	POWER
77-215	Dual 635nm "high powered" diode Class 2M	±3/32-in @ 30-ft (±2.5mm @ 9m)	Up to 100-ft (30m) dependent on illumination of area	± 4°	Single (± 10%)	3 AAA batteries, 1.5V (included)

EDP#	CONTENTS	WARRANTY
77-215	CL2XT Indoor/Outdoor Package. Includes: Indoor/Outdoor Package-magnetic laser tripod, batteries, hard-shell carrying case	1

Stanley® CL90 Cross Line Laser with Laser Pole

The CL90 features a heavy-duty, magnetically dampened compensator to self-level fast! "Out of leveling range" sensor triggers beams to automatically shut off when unit is moved out of its broad ±5° self-leveling range.

The CL90 features two output windows: one projects a laser cross, the second projects a 90°/plumb line reference.

- One button, four features: laser cross, 90° vertical line, laser cross with 90° vertical, and manual mode
- Beams blink when "Out-of-Level", alerts user
- 4-section laser pole with platform adjusts laser from 4-in (10cm) to 98" (250cm)
- Built for Interior Use



LEVELING ALIGNING SQUARING



EDP#	LASER DIODE	LEVELING ACCURACY	WORKING RANGE	SELF LEVELING	POWER
77-155	635nm (Class 2M)	±1/8-in @ 30-ft (±3mm@10m)	Up to 32 ft (10m)	± 5°	3 "AA" Alkaline batteries

EDP#	CONTENTS	WARRANTY
77-155	CL90 Package. Includes: Laser pole with platform, wall/tripod mount. Graduated circle, batteries, carrying case	1