



BOSCH



2-Speed Impact Drill GSB 20-2 RE

- Sturdy metal gear housing for long lifetime .
- Bosch high-performance motor with high torque for hard drilling and screwdriving work, core cutting, holesawing and stirring .
- Anti-rotation mechanical overload clutch for high level of work safety .
- Single-sleeve quick-change chuck with Auto Lock for quick tool changes with one hand .
- Speed preselection with setting wheel .
- Rotating brush plate for constant power in reverse and forward rotation .
- Softgrip for a secure hold .
- Ball grommet for high movement radius and for preventing cable breaks .
- Spindle collar diameter of 43 mm (European standard) – can be used in drill stands .

GSB 20-2 RE Professional

Technical data

Rated power input: 800 W

No-load speed: 0 – 1.100 / 3.000 rpm

Power output: 420 W

Weight: 2,50 kg

Torque (soft screwdriving application): 36,0 / 14,0 rpm

Rated torque: 5,2 / 2,0 Nm

Drill spindle connecting thread: 1/2" - 20 UNF

Clamping range, max.: 13 mm

Length: 365,0 mm

Width: 77,0 mm

Height: 220,0 mm

Impact rate at no-load speed: 0 – 17.600 / 48.000 rpm

Drilling range

Drilling dia. in concrete: 20 / 13 mm

Drilling dia. in wood: 40 / 25 mm

Drilling dia. in steel: 13 / 8 mm

Drilling dia. in masonry: 22 / 16 mm