

## ANALOG MULTIMETER



CE

**ST-365 TR**

DC Volts : 0-0.01/0.5/2.5/10/50/250/1000V(20kΩ/V)  
 AC Volts : 0-10/50/250/1000V  
 DC mA : 50uA/2.5/25/250mA  
 OHMS : 2K/20K/200K/2M/20M (20 Mid-Scale)  
 Accuracy : ±3% F.S. DC. ±4% F.S. AC.  
 Sensitivity : 20K/V DC. 8K/V AC.  
 DB : -10 to ±50dB  
 Hfe : 0-1000  
 ICEO : 150uA, 1.5mA, 15mA, 150mA  
 LV : 3V  
 Dimension : 100 x 150 x 41mm  
 Weight : 300g  
 Power : Two "AA" 1.5V Battery.  
 One 006P 9V Battery.  
 ● IEC 1010-1 CAT.II 1000V



CE

**ST-360 TRn**

DC Volts : 0-0.01/0.5/2.5/10/50/250/1000V(20KΩ/V)  
 AC Volts : 0-10/50/250/1000V  
 DC mA : 50uA/2.5/25/250mA  
 OHMS : 2K/20K/2M/20M (20 Mid-Scale)  
 Accuracy : ±3% F.S. DC. ±4% F.S. AC.  
 Sensitivity : 20K/V DC. 8K/V AC.  
 Db : -10 to ±50dB  
 Hfe : 0-1000  
 ICEO : 150uA, 15mA, 150mA  
 Lv : 3V  
 Dimension : 102 x 148 x 46mm  
 Weight : 300g  
 Power : Two "AA" 1.5V Battery.  
 One 006P 9V Battery.  
 ● IEC 1010-1 CAT.II 1000V



**ST-505**

● High quality Taut Band movement.  
 DCV : 0-0.25/1/2.5/10/50/250/1000V (50KΩ/V) ±2%  
 ACV : 0-2.5/10/50/250/1000V (10KΩ/V) ±3%  
 DCA : 0-25uA/1/25/500mA/10A(250mV drop) ±2%  
 ACA : 0-10A(250mV drop) ±3%  
 Resistance : 20KΩ, 200KΩ, 2MΩ, 20MΩ  
 (Midscale 100Ω)  
 Decibel : -20 to 62dB  
 Dimension : 145 x 101 x 47mm  
 Weight : 550g  
 Battery : 1.5V x 2



**ST-520**

DCV : 0-0.25/1/2.5/10/25/100/250/1000V  
 (50KΩ/V) ±3%  
 ACV : 0-2.5/10/25/100/250/500/1000V  
 (13KΩ/V) ±4%  
 DCA : 0.05/5/50/500mA. 0-12 ±3%  
 Resistance : 2KΩ, 20KΩ, 2MΩ, 20MΩ  
 (Midscale 20, 200, 20k, 200kΩ)  
 Decibel : -20 to 56dB(0dB=1Mw, 600Ω)  
 Dimension : 110 x 160 x 52mm  
 Weight : 480g  
 Battery : 1.5V x 2, 9V x 1  
 For telecom and audio work.