

Hitachi Koki

DV 20VB2 20mm(3/4") Impact Drill



- Class-top drilling speed and 790W Powerful motor
- Compact (333mm (13-1/8")) in entire length) and 2.2Kg (4.9 lbs.) lightweight for less user fatigue
- Aluminum die-casting inner cover and gear cover for increased durability
- Easy-to-operate 2-finger sized trigger switch with speed control dial
- Reliable and convenient push-button type forward/reverse changeover switch
- Easy-to-selected change lever for quick selection of impact drilling or drilling only mode
- Shortest chuck offset (23.5mm (15/16"))
- Soft grip handle for comfortable operation
- Slip clutch mechanism (for specific destinations)

Specifications:

Capacity	Concrete	Low speed: 20mm(3/4") High speed: 13mm(1/2")
	Steel	Low speed: 13mm(1/2") High speed: 8mm(5/16")
	Wood	Low speed: 40mm(1-9/16") High speed: 25mm(1")
Drill chuck	Mount type: UNF1/2"-20 Capacity: 13mm(1/2")	
Rated Power Input	790W	
No-Load Speed	Forward: Low: 0 - 1,000/min. High: 0 - 3,000/min.	
	Reverse: Low: 0 - 600/min. High: 0 - 1,800/min.	
No-Load Impact Rate	Low: 0 - 13,000/min. High: 0 - 39,000/min.	
Full-Load Impact Rate	Low: 8,000/min. High: 26,000/min.	
Overall Length	333mm(13-1/8") 339mm(13-11/32") with the slip clutch	
Net Weight	2.2 Kg (4.9 lbs.) without cord	
Standard Accessories	1 Chuck Wrench (for the keyed chuck only) 1 Side Handle 1 Depth Gauge 1 Plastic Carrying Case	