



P50A 1/4" - 2" pipes The compact lightweight body of the P50A combines high performance with maximum versatility. Ideal when it is necessary to thread pipe in many different locations - on site, repair work in factories, installation for domestic use and high rise construction.

Features include:-

Powerful 600W series motor which automatically increases power (torque) when the load increases or the voltage supplied drops - prevents stalling and damage to the motor.

- A die cast aluminium body - durable, corrosion resistant, long life.
- Automatic "triple" filter lubrication system feeds cutting oil to all dies - increases life of dies.
- Carbon brushes with automatic stop mechanism (approx 250 hrs) - prevents commutator damage, prolongs motor life.
- A patented Hammer Chuck with replaceable inserts - provides powerful non-slip grip.
- Fully enclosed oil tank which enables transportation without draining - no leaks and spills.
- Supplied with easy to follow operation and maintenance manual.

Standard Specification

Threading Capacity	1/4" - 2"
Motor	Single phase 600W Series Motor
Voltage	220V
Rotation Speed	40 rpm (unloaded)
Dimensions	590 (L) x 375 (W) x 395 (H) mm
Nett Weight	46 kg (101 lbs)

Standard Equipment Supplied

Description	
1/2" - 2" Uni-Auto V Die Head	
Dies	1/2" - 3/4" BSPT 1" - 2" BSPT
Pipe Cutter and Deburring Tool	
Thread Cutting Oil and Bearing Oil	

Optional Equipment Diehead and Dies for : 1/4" - 3/8" BSPT; 1/4" - 2" NPT; Bolts - BSW, UNC Metric, etc. HSS Dies for threading stainless steel.