
## KYOWA HYDRAUILIC PRESSURE TESTER







- High-precision stainless steel (SUS 304) ball value is applied as the valve.
- Valve seat is replaceable with ease.
- Water tank of rust-free plastic (P.P) construction assures unchanging cleanliness. (Models T-50K and T-100K are of vinyl-coated steel sheet construction.)
- The plunger packing used is standard product, O-ring No. P-22 which is available in local hardware dealers.
- All fulcrum pins applied are made of stainless steel.
- A full range of accessories are provided to permit on-the-spot job.
- Matchless compact and light-weight design in the world.



SPECIFICATIONS (50kg/cm<sup>2</sup> pressure gauge is available if desired.)

Model	Maximum Pressure	Plunger Diameter	Stroke	Rate of Water Suction Per Stroke	Capacity of Water Tank		Weight	Dimension L x H x W	Accessories	
T-50K-P	50kg/cm <sup>2</sup>	22 <sup>m</sup> / <sub>m</sub>	35 <sup>m</sup> / <sub>m</sub>	13 c.c.	4.5 ℓ Plastic Tank	1/4	3.3kg	320x300x200 <sup>m</sup> / <sub>m</sub>	Pressure gauge 1/4 PT Pressure hose Union joint 1/2 Bushing 1/2 x 1/4	1 1 1
T-100KP	100kg/cm <sup>2</sup>	22 <sup>m</sup> / <sub>m</sub>	35 <sup>m</sup> / <sub>m</sub>	13 c.c.	5.2 ℓ Plastic Tank	1/4	7.0kg	370x300x210 <sup>m</sup> / <sub>m</sub>	Pressure gauge 1/4 PT Ultra high pressure hose 1/4 PF x 1m 1/4 nipple	1 1 1